



SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date: 10.03.2017 Date issued: January, 2011 Page 1/76

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Substance Identification

Trade name	Iso-Butanol
IUPAC name	2-Methyl-1-propanol
Synonym	Isobutyl Alcohol, Isopropylcarbinol
EINECS (EC no)	201-148-0
CAS no	78-83-1
Index no.	603-108-00-1
Molecular Formula	(CH ₃) ₂ CH-CH ₂ OH
Molecular weight	74.12
REACH Registration number	01-2119484609-23-0009
Type of substance	Organic Mono-constituent substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

The main use of isobutanol is as raw material in isobutyl acetate manufacture for use in the lacquer industry.

It is used as a flavouring agent in butter, cola, fruit, liquor, rum, and whisky.

Isobutanol is also used in the industrial synthesis of derivative esters.

Other application: solvent in paint, varnish removers and inks, chemical extractant in the production of organic compound, and as mobil phase in thin layer chromatography.

Relevant identified uses

Industrial use [SU3, SU8, SU9] Manufacturing of substances [PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15]

Industrial use [SU3, SU8, SU9]; Use as intermediate [PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9]

Industrial use [SU3, SU10] Formulation & Repacking of substances and mixture (PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC 9, PROC15)

Industrial use [SU3, SU8, SU9]; Distribution of substance [PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15]

Industrial use [SU3] Use in coatings (paints, ink, toners, adhesives) [PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15]

Industrial use [SU3] ; Use cleaning agents [PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13]

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 2/76

Industrial use [SU3] ; Use in lubricants [PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18]
Industrial use [SU3]; Metal working fluids/rolling oils [PROC1, PROC2, PROC3, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17]
Professional use [SU 22]; Distribution of the substance [PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15]
Professional use [SU 22]; Use in coatings (paints, ink, toners, adhesives) [PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19]
Professional use [SU 22]; Use cleaning agents [PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11]
Professional use [SU 22]; Use in lubricants [PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20]
Professional use [SU 22]; Metal working fluids/rolling oils [PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC17]
Professional use [SU 22]; Use in laboratories [PROC10, PROC15]
Consumer Use [21]; Use in coatings (paints, ink, toners, adhesives) [PC1, PC4, PC9, PC15, PC18, PC23, PC24, PC31]
Consumer Use [21]; Use cleaning agents [PC4, PC9, PC24, PC35, PC38]
Consumer Use [21]; Use in lubricants [PC1, PC24, PC31, PC35]
Consumer Use [21]; Use as consumer care product or disinfectant [PC28, PC39]

Uses advised against: No uses advised against.

1.3. Details of the supplier of the safety data sheet

Name	S.C. OLTCHIM S.A
Address	1 Uzinei Street, 240050 Ramnicu Valcea, Romania
Phone N°	+40 250 701 200
FAX N°	+40 250 735 030
E-mail of competent person responsible for SDS in the MS or in the EU:	tehnic@oltchim.com

1.4. Emergency telephone number

European Emergency N°:	112
Emergency telephone at the company:	+40/250/738141- available 24h/day/365days
For Romania- The institution responsible with providing information in case of a health emergency is The National Institute for Public Health, Department for the	Telephone: 021.318.36.06, Opening hours: Monday - Friday from 8 a.m. to 3 p.m.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 3/76

International Sanitary Regulation and
Toxicological Information.

2. HAZARD IDENTIFICATION

2.1. Classification of the substances or the mixture

2.1.1. Classification according to Regulation (EC) 1272/2008 (CLP)

Flam. Liquid 3 ; H226

Skin Irritation 2 ; H315

Eye Damage 1; H318

STOT Single Exp. 3; H335

STOT Single Exp. 3; H336

2.2. Label elements

Labeling according to Regulation (EC) 1272/2008

Signal word: Danger

Hazard pictogram:

GHS02: flame



GHS05: corrosion



GHS07: exclamation mark



Hazard statements:



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 4/76

H226: Flammable liquid and vapour.
H335: May cause respiratory irritation.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378: In case of fire: Use water spray, dry extinguishing media, alcohol-resistant foam, carbon dioxide for extinction.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of absorbed material in accordance with regulations.

2.3. Other effects

The substance does not fulfil the PBT criteria (not PBT) and not the vPvB criteria (not vPvB). iso-Butanol is a volatile, combustible and flammable liquid that should be stored in well-ventilated areas. Dangerous fire hazard when exposed to heat, flame and oxidizers. Vapor-air mixtures are explosive above flash point.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS	EC No.	Index no.	Concentration (%)
Iso-Butanol	78-83-1	201-148-0	603-108-00-1	Min.99.5

Impurities

No impurities relevant for classification and labeling.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 5/76

4 . FIRST - AID MEASURES

4.1 Description of first aid measures

General Advice: IF exposed or if you feel unwell: Call a Poison Center or doctor/physician. Show this safety data sheet to the doctor in attendance.

Following inhation: Remove to fresh air and rest in half upright position. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Keep person warm and at rest. Call a physician.

Following skin contact: Wash the contaminated skin with plenty of soap or mild detergent and water for at least 15 minutes while removing contaminated clothing and shoes. If irritation persists after washing, get medical attention.

Following eye contact: Wash the eyes immediately with large amount of water lifting the upper and lower lids, until no evidence of chemical remains at least 15-20 minutes. If irritation persists after washing get medical attention. Contact lenses should not worn with this product.

Following ingestion: Remove ingested material by gastric lavage or emesis. Give artificial respiration with oxygen if respiration is depressed. Get medical attention. **Administration of gastric lavage is permitted only by qualified medic personnel.**

4.2. Most important symptoms and effects, both acute and delayed

By eye contact: Vapors concentration >100ppm may cause irritation, redness pain and blurred vision.

By skin contact: Irritant. Contact with vapors or liquid may cause mild to moderate irritation and redness. The substance caused slight erythema and hyperemia but without the formation of wheals.

By ingestion: May cause abdominal pain, headache, nausea and diarrhoea. Large doses affect liver and kidneys. May have narcotic effect. Ingestion may also lead to alcohol poisoning.

By inhalation: Iso-butanol is irritant/narcotic. Inhalation of high concentrations of vapors may cause irritation of the respiratory tract with sore throat, coughing, shortness of breath, headaches, nausea, dizziness, dullness, narcosis and unconsciousness.

Chronic effects: Prolonged inhalation has caused auditory nerve and vestibular injury resulting in severe vertigo and hearing loss in workers exposed to iso-Butanol. Repeated or prolonged contact may degrease the skin resulting in drying, cracking and eczematoid dermatitis. Person with pre-



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 6/76

existing skin disorders or eye problems or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4.3 Indication of immediate medical attention and special treatment needed

Treat symptomatically and supportively.

5. FIRE - FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Dry chemical powder extinguishers are recommended. These are particularly useful when fires involve "live" electrical equipment, because the powder is non-conducting. For a small fire, use carbon dioxide, dry chemical powder, alcohol-resistant foam, sand, earth, or water spray. Do not use water in a jet. For a large fire, use alcohol-resistant foam, or water fog.

Unsuitable extinguishing media: Do not use water streams, since the streams will scatter and spread the fire. For maintaining the tanks cool, use sprayed water.

5.2 Special hazards arising from the substance or mixture

Exposure hazards: iso-Butanol is a combustible and flammable liquid, sensible to static discharges. Dangerous fire hazard when exposed to heat and flame. Vapor-air mixtures are explosive above flash point. In the event of a fire, move the containers from fire area if you can do it without risks. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks. For massive fire in cargo area, use unmanned hose holder or monitor nozzles; if this is impossible, withdraw from the area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to. Isolate for 1/2 mile in all directions if tank, rail car or tank truck is involved in fire.

Hazardous combustion products: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Protection of fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 7/76

Remarks: FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Empty container very hazardous!

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep unnecessary and unprotected personnel away from entering. Avoid contact with skin, eyes, and clothing – wear suitable protective equipment (see section 8). Do not touch or walk through spill material. Shut off all ignition sources.

For emergency responders: Ventilate area of leak or spill. Persons performing clean-up work should wear adequate personal protective equipment and a self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Remove all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Stop leak and use water spray to reduce vapors. Prevent from contamination the ground and the surface waters by isolating the hazard area. Contain and recover liquid when possible. Keep closed containers and dispose according to all applicable federal, state or local environment regulations.

6.3. Methods and materials for containment and cleaning up

Methods of cleaning up: Contain and recover liquid when possible. Use water spray to reduce vapors.

For small spills: absorb the spilt liquid with sand, earth or other absorbent material(e.g.vermiculite) and place in a chemical waste container for subsequent disposal by burning. Flush the contaminated area with plenty of water.

For large spills: Prevent spilt liquid from spreading by the use of sand or earth. If possible, transfer the liquid to a salvage tank. Otherwise, treat as for a small spillage. Inform the local authorities (particularly the fire service) at once, if the spilt liquid enters the surface drains, since a potential explosive hazard will be created.

Special precautions: Do not use combustible materials as absorbent, such as saw dust. Do not flush to sewer! Use only non sparking tools and equipment.

6.4. Reference to other sections: Additional advice: Refer to section 8, 13.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 8/76

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Protective measures: Protect against physical damage. Sources of ignition such as smoking and open flames are prohibited where iso-butanol is used, handled or stored in a manner that could create a potential fire or explosion hazard. Metal containers should be bonded and grounded for transfers to avoid static sparks. When handling this product use non-sparking type tools and equipment, including proof ventilation. Do not use compressed air or oxygen for filling, discharging or handling. The personnel which handling the product must wear protective equipment.

Advice on general occupational hygiene: Avoid inhalation or ingestion and contact with skin and eyes. General occupational hygiene measures are required to ensure safe handling of the substance. These measures involve good personal and housekeeping practices (i.e. regular cleaning with suitable cleaning devices), no drinking, eating and smoking at the workplace. Shower and change clothes at end of work shift. Do not wear contaminated clothing at home.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Store in a cool, dry well-ventilated location, away from any area where fire may be acute. Outside or detached storage is preferred. Separate from incompatibles. Storage and use area should be No Smoking areas. Drums must be equipped with self-closing valves, nitrogen blanket. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

Incompatible materials: alkali metals, inorganic acids, oxidizers, acetaldehyde, isocyanates, chlorine.
Incompatible materials for storage: aluminium, plastics, rubber are attacked.

Iso-Butanol Self life: 6 months.

7.3. Specific end use(s)

Please check the identified uses from Section 1.2.

For more information please see the relevant exposure scenario, available via your supplier/given in the Annex I.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 9/76

8 . EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

8.1.1. Occupational Exposure limit values

	Limit value -8h mg/m ³	Limit values-Short term mg/m ³
Austria	150	600
Belgium	154	150
Denmark	150	310
France	150	
Germany	310	
Poland	100	200
Spain	154	
Switzerland	150	150
UK	154	231

8.1.2. Information on monitoring procedures

Substance name: iso-Butanol - EC no: 201-148-0; CAS no.: 78-83-1

DNEL(s) for workers

Route	Type of effect	Hazard conclusion
Inhalation	Systemic effects - Long-term	
Inhalation	Systemic effects - Acute	
Inhalation	Local effects - Long-term	DNEL (Derived No Effect Level): 310 mg/m ³
Inhalation	Local effects - Acute	
Dermal	Systemic effects - Long-term	No hazard identified
Dermal	Systemic effects - Acute	No hazard identified
Dermal	Local effects - Long-term	Low hazard (no threshold derived)
Dermal	Local effects - Acute	
Eyes	Local effects	Medium hazard (no threshold derived)



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 10/76

DNEL(s) for population

Route	Type of effect	Hazard conclusion
Inhalation	Systemic effects - Long-term	
Inhalation	Systemic effects - Acute	
Inhalation	Local effects - Long-term	DNEL (Derived No Effect Level): 55 mg/m ³
Inhalation	Local effects - Acute	
Dermal	Systemic effects - Long-term	No hazard identified
Dermal	Systemic effects - Acute	No hazard identified
Dermal	Local effects - Long-term	Low hazard (no threshold derived)
Dermal	Local effects - Acute	Low hazard (no threshold derived)
Oral	Systemic effects - Long-term	No hazard identified
Oral	Systemic effects - Acute	No hazard identified
Eyes	Local effects	Medium hazard (no threshold derived)

PNECs

Environmental protection target	PNEC
Freshwater (mg/l)	0.4
Freshwater sediments (mg/kg ww)	1.52
Marine water (mg/l)	0.04
Marine sediments (mg/kg sediment dw)	0.152
Soil (mg/kg soil dw)	0.0699
STP (mg/l)	10

Refer to section 11 and 12 of the SDS for information on PNEC and DNEL derivation. Guidance on how to comply with these DNELs and PNECs is given in the attached Exposure Scenarios, in the annex.

8.2. Exposure control

8.2.1. Engineering controls: A system of local and/or general exhaust is recommended to keep employee exposure as low as possible. Local extract ventilation is generally preferred because it can control the emissions of the contaminant at its sources, preventing dispersions of it into the general



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 11/76

work area. Ventilation equipment should be explosion- proof if explosive concentration of vapors or fume are present.

8.2.2. Personal Protection Equipment

Eye / Face protection : Use chemical safety goggles and/or a full face shield where splashing is possible. Avoid using contact lenses at work. Equipment for eye protection should be tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).The working area will be equipped with eyewash fountains

Skin protection: Complete suit protecting against chemicals (solvent resistant). Flame retardant antistatic protective clothing.The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Do not take contaminated work clothes home, family members could be exposed.

Hand protection: Gloves tightness must be check before use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Recommended material: nitril rubber, neoprene rubber

The following materials are suitable for protective gloves (Permeation time \geq 8 hours):

Polychloroprene - CR (0,5 mm)

Nitrile rubber/Nitrile latex - NBR (0,35 mm)

Butyl rubber - Butyl (0,5 mm)

Fluoro carbon rubber - FKM (0,4 mm)

Natural rubber and PVC are unsuitable for protective gloves because of degradation, severe swelling or low permeation time.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Above recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Respiratory protection: If the exposure limit is exceeded, wear a supplied air, full-face piece self contained breathing apparatus.

Organic vapor respirator with a particulate pre-filter may be worn if vapors are detected or irritating. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 13/76

10.2. Chemical stability: Stable under ordinary conditions of use and storage.

10.3. Possibility of hazardous reactions:

- alkali metals: reacts with formation of flammable hydrogen gas;
- inorganic acids: hazardous of explosion;
- oxidizers (strong): reacts with formation of flammable hydrogen gas;
- acetaldehyde: violent condensation reaction;
- isocyanates: possible explosion in absence of solvent;
- chlorine: formation of highly explosion alkyl hypochlorites.

10.4. Conditions to avoid: Heat, sparks, electric equipment & open flame.

10.5. Incompatible materials: Oxidizing agents (such as chromium trioxide), reducing agents, acids and bases, amines.

Iso-butanol may react at high temperatures with aluminum (metallic). Also iso-butanol could attack plastics and rubber.

11. TOXICOLOGICAL INFORMATION

	Conclusions
Absorbtion	no bioaccumulation potential based on study results.
Acute toxicity	<p><u>Oral route:</u> Rat: LD50 = >2830 mg/kg bw (males) / 3350 mg/kg bw (females; GLP, OECD 401 Mouse: LD50 = 3500 mg/kg bw (Kushneva et al. 1983, Val. 4)</p> <p><u>Inhalation route:</u> Rat, 6 h: LC0 >= 18.2 mg/L (GLP, neurotoxicity guideline, CMA 1994) Rat, 4 h: LC50 = 19.6 mg/L; irritation of the respiratory tract (Kushneva et al. 1983, Val. 4) Mouse, 4 h: LC50 = 15.5 mg/L (Kushneva et al. 1983, Val. 4) Guinea pig, 4 h: LC50 = 19.9 mg/L (Kushneva et al. 1983, Val. 4)</p> <p><u>Dermal route:</u> Rabbit: LD50 = > 2000 mg/kg bw (males); 2460 mg/kg bw (females; GLP, OECD 402; Union Carbide Corporation 1993)</p>



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 14/76

	<p>The available data for isobutanol indicate a relative low potential for acute toxicity; the substance has not to be classified according to 67/548/EEC and 1272/2008/EC (CLP) requirements.</p>
Irritation/Corrosion	<p><u>Skin</u> Results of the available studies led to the classification as skin irritant (R38) according to Annex I of 67/548/EEC, corresponding to skin irritation Cat. 2 following 1272/2008/EC (CLP) requirements.</p> <p><u>Eye</u> Due to the irreversible irritation effects on rabbit eyes, isobutanol has to be classified as posing the risk of serious eye damage according to Annex I of 67/548/EEC (R41) and as eye irritant Cat. 1 according to 1272/2008/EC (CLP) criteria.</p> <p><u>Respiratory tract</u> Due to the effects observed in an acute inhalation study, isobutanol has to be classified as irritant to the respiratory</p>
Sensitisation	<p>Due to the negative results of a QSAR calculation for isobutanol and of the analogous substance propan-1-ol in a guinea pig maximisation test, isobutanol has not to be classified as skin sensitizer according to 67/548/EEC and 1272/2008/EC (CLP) requirements.</p>
Repeated dose toxicity	<p><u>Oral route</u> 90 d, rat, drinking water: NOAEL \geq ca. 1450 mg/kg bw/ day (= 16000 ppm; no effects observed; OECD 408, GLP; BG Chemie 1990)</p> <p><u>Dermal route</u> 4-6 times 0.3 mL for 24 h within 7 d, rabbit, occlusive: no systemic toxicity studied; local: highly irritant (TSCATS OTS 0510692, 1986; Val. 4)</p> <p><u>Inhalation route</u> 90 d, rat, 6 h/d, 5 d/wk: NOAEL systemic \geq ca. 7.5 mg/L/day (2500 ppm); NOEL systemic = ca. 3.0 mg/L/day due to slight hematologic effects with questionable biological significance (GLP, neurotoxicity guideline, CMA 1996a)</p>



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 15/76

	<p>2-gen study/ca. 17 wks for the parental generation, 6 h/d, 7 d/wk: NOAEL systemic \geq ca. 7.5 mg/L/day (2500 ppm, no effects observed; GLP, EPA OPPTS 870.3800; ACC 2003)</p> <p>There is currently no need for classification of effects according to 67/548/EEC and 1272/2008/EC (CLP) requirements due to repeated exposure to the test substance.</p>
Mutagenity	<p>Iso-butanol was not genotoxic in vitro experiments using human, rodent, and bacterial cells or in vivo experiments in mice. For isobutanol, there is therefore no need for classification for mutagenic effects according to 67/548/EEC and 1272/2008/EC (CLP) requirements.</p>
Carcinogenity	<p>Due to the lack of a carcinogenic potential of isobutanol, there is currently no need for classification and labeling.</p>
Toxicity for reproduction	<p>Due to the lack of toxicity on fertility and development in definite studies with isobutanol, there is no need for classification according to reproductive toxicity according to 67/548/EEC and 1272/2008/EC (CLP) requirements.</p>

12. ECOLOGICAL INFORMATIONS

12.1. Toxicity

Acute (short-term) toxicity

Fish

Pimephales promelas/Fresh water/ flow-through LC50 (96 h)= 1430 mg/L

Iso-butanol is acutely not harmful to fish.

Aquatic invertebrates

Daphnia pulex/freshwater/static EC50 (48 h) \geq 1100 mg/L

Iso-butanol is acutely not harmful to aquatic invertebrates.

Algae and aquatic plants

Pseudokirchnerella subcapitata (algae)/freshwater/static EC50 (72 h): 1799 mg/L test mat. And the NOEC (72 h)= 53 mg/L (OECD 201)

Chronic (long-term) toxicity

Fish

No data on long-term toxicity on fish are available.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 16/76

Aquatic invertebrates:

Daphnia magna/ freshwater

NOEC (21 d): 20 mg/L test mat.

Scenedesmus subspicatus (new name: *Desmodesmus subspicatus*) (algae)/freshwater/static
EC50 (48h) of 2300 mg/L and a NOEC of approximately 900 mg/L (EC10).

Iso-butanol is acutely not harmful to aquatic algae.

Toxicity to sediment

No data on sediment toxicity are available.

Toxicity to soil macro-organisms

The substance exhibits low potential for adsorption to soil, is not bioaccumulative and is readily biodegradable. This means that the substance will be rapidly mineralized by microorganisms in soil.

Toxicity to terrestrial plants:

Is not harmful to plants.

12.2. Persistence and degradability:

Abiotic degradation: substance is readily biodegradable.

Biodegradation: The test substance is readily biodegradable according to OECD criteria.

12.3. Bioaccumulative potential: Regarding the 1-octanol/water partition coefficient, accumulation of the test substance in organisms is not to be expected.

Secondary poisoning: Due to the logPow, significant accumulation in organisms is not expected. Therefore, secondary poisoning is of no concern for this substance.

12.4. Mobility

Iso-butanol will preferentially distributed into the compartments water and air.

Air: After evaporation or exposure to the air, the product will be slowly degraded by photochemical processes with half-life (t1/2) of about 56 hours.

Water: Iso-butanol will slowly evaporate from the water surface into the atmosphere.

iso-Butanol is readily biodegradable in water. In a simulation test according to OECD guideline 303A iso-butanol show a biodegradation degree of 90-100 % (DOC) after 35 days.

Soil and sediments: Based upon a calculated log Koc adsorption to solid soil phase is not expected.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 17/76

12.5. Results of PBT and vPvB assessment:

Iso-Butanol does not fulfil the PBT criteria (not PBT) and not the vPvB criteria (not vPvB).

PBT : No.

P: No. B: No. T: Yes.

vPvB : No.

vP: No. vB: No

13. DISPOSAL CONSIDERATIONS

This section contains generic advice and guidance.

13.1 Waste treatment methods

13.1.1 Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

Waste Code: No waste key number as per the European Waste Types List can be assigned to this product, since such classification is based on the (as yet undetermined) use to which the product is put by the consumer.

13.1.2. Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Relevant European legislation regarding waste:

Directive 2008/98/EC on waste (Waste framework Directive)

Directive 2008/532/EC replacing Decision 94/3/EC establishing a list of wastes pursuant to Article 1(a) of Council Directive 75/442/EEC on waste and Council Decision 94/904/EC establishing a list of hazardous waste pursuant to Article 1(4) of Council Directive 91/689/EEC on hazardous waste Regulation (Ec) No 1013/2006 of the European Parliament and of the Council on shipments of waste, with subsequent modifications and additions



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 18/76

14. TRANSPORT INFORMATION

Iso-butanol can be shipped according to transport regulations for dangerous goods, hazard class 3, Flammable liquids.

Transport Labeling



Label no.3
Flammable liquids

RID/ADR

UN No.	1212
Proper shipping name	iso-Butanol
Hazard class	3
UN Packing Group	III
Classification code	F1

Danger panel 30/1212 (*Hazard Identification No.* 30)
(UN Identification No 1212)

IMDG/IMO

UN No.	1212
Hazard class	3
UN Packing Group	III
Proper shipping name	iso-Butanol
EmS No.	F-E, S-D
Marine pollutant	No

IATA/IT-ICAO

Proper shipping name	iso-Butanols
UN No.	1212
Hazard class	3
UN Packing Group	III
IATA Label	Flammable Liquid
Packaging Note Passenger	309
Packaging Note Cargo	310



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 19/76

Max. Quantity Passenger 60 l

Max. Quantity Cargo 220 l

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant information regarding the European legislation

EU Regulation (EC) No. 1907/2006 (REACH) Regulation (EC) no.1907/2006 of the European Parliament and of the Council regarding the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) Regulation

Regulation (EC) no.1272/2008 of the European Parliament and of the Council on the Classification, Labeling and Packaging of substances and mixtures.

Directive 2012/18/EU (SEVESO III) of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances, amending and subsequently repealing Council Directive 96/82/EC

Regulation (EC) No 1005/2009 of the European Parliament and of the Council on substances that deplete the ozone layer

European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

Regulation referring to the International Carriage of Dangerous Goods by Rail (RID)

International Maritime Dangerous Goods (IMDG)

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern (Authorizations): iso-Butanol is not subject to authorization

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Restrictions on use: see Restriction 40 from Annex XVII.

Directive 2012/18/EU -SEVESO III Directive- iso-Butanol is listed on Annex I Part 1 in Sections P5a, P5b, P5c.

WGK (Germany): WGK 1 low hazard to water

Other EU regulations: iso-Butanol is not subject to:

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pollutants

Regulation (EC) No 649/2012 concerning the export and import of dangerous chemicals



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 20/76

15.2 Chemical safety Assessment Assessment

A chemical safety assessment has been carried out for this substance and a CSR was issued.

16. OTHER INFORMATION

16.1. Full text of H-Statements referred to under above sections

H226: Flammable liquid and vapour.
H335: May cause respiratory irritation.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.

16. 2. Abbreviation and acronyms (NOT ALL ARE USED IN THIS SDS)

ADR European agreement concerning the international carriage of dangerous goods by road
BSAF Bio soil accumulation factor
BCF Bio concentration factor
CAS Chemical Abstracts Service
CLP Classification, labelling and packaging
CMR Carcinogenic, mutagenic or toxic for reproduction
CSA/CSR Chemical safety assessment / Chemical safety report
DNEL Derived no effect level
EC10 Concentration of a substance where 10% of the population is affected
EC50 Concentration of a substance where 50% of the population is affected
ECHA European chemicals agency
EINECS EU list of existing chemical substances
EmS Emergency schedule
ERC Environmental release category
ES Exposure scenario
eSDS Extended safety data sheet
GHS Globally harmonised system
IATA-DGR International air transport association - dangerous goods regulations
ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air
IU Identified use
IUPAC International Union of Pure and Applied Chemistry
IBC code International code for the construction and equipment of ships carrying dangerous chemicals in bulk
IMDG International maritime dangerous goods
KP Partition coefficient



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 21/76

LC10 Lethal concentration of a substance that can be expected to cause death in 10% of the population

LC50 Lethal concentration of a substance that can be expected to cause death in 50% of the population

LD50 Lethal dose of a substance that can be expected to cause death in 50% of the population

NO(A)EC No observed (adverse) effect concentration

NO(A)EL No observed (adverse) effect level

OECD Organisation for economic co-operation and development

OEL Occupational exposure limit

PBT Persistent, bioaccumulative, and toxic

PC Product category

PNEC Predicted no-effect concentration

PROC Process category

REACH Registration, evaluation, authorisation and restriction of chemicals (i.e. Regulation (EC) No. 1907/2006)

RID International rule for transport of dangerous substances by railway

SDS Safety data sheet

STOT Specific target organ toxicant

STP Sewage treatment plant

SU Sector of end use

TWA Time weighted average

vPvB Very persistent, very bioaccumulative

16.3. Key literature references

The information provided in this eSDS is consistent with the information provided in the REACH CSR. The CSR contains a complete reference list for all data used. Non confidential data from the REACH registration dossier are published by the ECHA, see <https://echa.europa.eu/information-on-chemicals/registered-substances>, http://echa.europa.eu/clp/c_1_inventory_en.asp
<http://chelist.jrc.ec.europa.eu>
<http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp> (GESTIS chemicals database)

16.4. Revision: Revision 4 replace revision dated November 23, 2015

Section 1.2, 3, 8, 12, 15, 16 of this safety data sheet have been revised according to the provision of Regulation (EC) No. 1907/2006, as amended by Regulation 830/2015. The information provided in this SDS is consistent with the information provided in the REACH CSR for iso-butanol.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 22/76

Disclaimer:

Oltchim provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. Furthermore, this safety data sheet is made up based on the legal requirements as set by EC 1907/2006 (REACH) and EC Regulation 830/2015.

ANNEX I –EXPOSURE SCENARIO

1. ES1 - Manufacture of isobutanol (Industrial)

Section 1	Exposure Scenario Title
Title	Manufacture of i-Butanol; CAS: 78-83-1
Use Descriptor	Sector of Use: Industrial (SU8, SU9)



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 23/76

	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15	
	Environmental Release Categories: ERC1, ERC4, ERC6a	
Processes, tasks, activities covered	Use as process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities	
Section 2	Operational conditions and risk management measures	
Section 2.1	Control of worker exposure	
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date: 10.03.2017 Date issued: January, 2011 Page 24/76

General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82]	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81]	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1

#1 refers to qualitative assessment

2. ES2 – Use as intermediate (Industrial)

Section 1	Exposure Scenario Title
Title	Use as intermediate; CAS: 78-83-1
Use Descriptor	Sector of Use: Industrial (SU8, SU9)
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9
	Environmental Release Categories: ERC6a
Processes, tasks, activities covered	Use as intermediate. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container),



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 25/76

		sampling and associated laboratory activities
Section 2	Operational conditions and risk management measures	
Section 2.1	Control of worker exposure	
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases.#1 Avoid frequent and direct contact with substance.#1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed.#1 Use suitable eye protection and gloves [PPE14].#1
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases.#1 Avoid frequent and direct contact with substance.#1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed.#1 Use suitable eye protection and gloves [PPE14].#1
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases.#1 Avoid frequent and direct contact with substance.#1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed.#1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 26/76

		Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}

^{#1} refers to qualitative assessment

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 27/76

3. ES3 – Formulation & (re)packing of substances and mixtures (Industrial)

Section 1		Exposure Scenario Title
Title		Formulation & (re)packing of substances and mixtures; CAS: 78-83-1
Use Descriptor		Sector of Use: Industrial (SU10)
		Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
		Environmental Release Categories: ERC 2
Processes, tasks, activities covered		Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, large and small scale packing, maintenance and associated laboratory activities
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product		Liquid, vapour pressure 0.5 - 10 kPa [OC4].
Concentration of substance in product		Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
Amounts used		<i>Not applicable</i>
Frequency and duration of use		Covers daily exposures up to 8 hours (unless stated differently) [G2]
Human factors not influenced by risk management		<i>Not applicable</i>
Other Operational Conditions affecting worker exposure		Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 28/76

General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Batch process [CS55]. Mixing operations (open systems) [CS30].	5	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 29/76

Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1

#1 refers to qualitative assessment

4. ES4 – Distribution of substance (Industrial)

Section 1		Exposure Scenario Title
Title	Distribution of substance; CAS: 78-83-1	
Use Descriptor	Sector of Use: Industrial (SU8, SU9)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15	
	Environmental Release Categories: ERC1, ERC2	
Processes, tasks, activities covered	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its distribution and associated laboratory activities	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 30/76

Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. ; Continuous process [CS54]. With sample collection [CS56]. ; Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Batch process [CS55]. ; With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (open systems) [CS16]. Batch process [CS55]. ; With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82]	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81]	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Pouring from small containers [CS9]. Dedicated facility [CS81]	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 31/76

Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMS in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
--	----	---

#1 refers to qualitative assessment

5. ES 4 – Distribution of substance (Professional)

Section 1		Exposure Scenario Title
Title	Distribution of substance; CAS: 78-83-1	
Use Descriptor	Sector of Use: Professional (SU22)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15	
	Environmental Release Categories: ERC1, ERC2	
Processes, tasks, activities covered	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its distribution and associated laboratory activities	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 32/76

General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 33/76

^{#1} refers to qualitative assessment**6. ES5 – Use in coatings (paints, ink, toners, adhesives; Industrial)**

Section 1		Exposure Scenario Title
Title	Use in coatings (paints, ink, toners, adhesives); CAS: 78-83-1	
Use Descriptor	Sector of Use: Industrial (SU3)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC15;	
	Environmental Release Categories: ERC4	
Processes, tasks, activities covered	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated	



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 34/76

		differently) [G13].
Amounts used		<i>Not applicable</i>
Frequency and duration of use		Covers daily exposures up to 8 hours (unless stated differently) [G2]
Human factors not influenced by risk management		<i>Not applicable</i>
Other Operational Conditions affecting worker exposure		Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 35/76

		RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Batch process [CS55]. Mixing operations (open systems) [CS30].	5	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Spraying [CS10].	7#2	Use in a spraying booth. Minimization of manual phases. #1 Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 36/76

Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Rolling, Brushing [CS51].	10	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Dipping, immersion and pouring [CS4].	13	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 37/76

Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
---	----	---

#1 refers to qualitative assessment

#2 other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)

7. ES5 – Use in coatings (paints, ink, toners, adhesives; Professional)

Section 1	Exposure Scenario Title
Title	Use in coatings (paints, ink, toners, adhesives); CAS: 78-83-1
Use Descriptor	Sector of Use: Professional (SU22)
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC 9, PROC10, PROC11, PROC13, PROC15, PROC19;
	Environmental Release Categories: ERC8a, ERC8c, ERC8d, ERC8f
Processes, tasks, activities covered	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 38/76

Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 39/76

Batch process [CS55]. Mixing operations (open systems) [CS30].	5	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Rolling, Brushing [CS51].	10	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Spraying [CS10].	11 ^{#2}	Use in a spraying booth. Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 40/76

		<p>Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 47%) Minimization of manual phases. #1 Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1</p> <p>Provide enhanced mechanical ventilation by mechanical means [E48].(effectiveness general ventilation: 47%) Minimization of manual phases. #1 Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1 Wear a suitable respiratory protection (effectiveness: 80%). If no adequate respiratory protection is available, avoid carrying out operation for more than 2 hours.</p>
Dipping, immersion and pouring [CS4].	13	<p>Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1</p>
Laboratory activities [CS36]. Small scale [CS61].	15	<p>Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1</p>
Hand-mixing with intimate contact. Only PPE.	19	<p>Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1</p>

#1 refers to qualitative assessment

#2 other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 41/76

8. ES5 – Use in coatings (paints, ink, toners, adhesives; Consumer)

In general, it is assumed that there is no use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing isobutanol.

It is assumed that lubricants, greases usually are contained in closed systems in machines and other equipment. Exposure arising from the use of machines and other equipment and arising from short and only occasional periods of manual handling (e.g. pouring of lubricants, greases) is considered to be negligible.

Section 1		Exposure Scenario Title
Title		Use in coatings (paints, ink, toners, adhesives)
Sector of Use (SU code)		21
Use Descriptor (PC codes)		PC1, PC4, PC9, PC15, PC18, PC23, PC24, PC31
Processes, tasks, activities covered		Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning.
Environmental Release Category		ERC8a, ERC8c, ERC8d, ERC8f
Specific Environmental Release Category		
Section 2		Operational conditions and risk management measures
Section 2.1		Control of consumer exposure
Product characteristics		
Physical form of product		liquid
Vapour pressure (Pa)		1600
Concentration of substance in product		Unless otherwise stated, covers concentration up to 50% [ConsOC1]
Amounts used		Unless otherwise stated, covers use amounts up to 9000g [ConsOC2];
Frequency and duration of use/exposure		Unless otherwise stated, covers use frequency up to 1 times per day [ConsOC4]; covers exposure up to 6 hours per event [ConsOC14]
Other Operational Conditions affecting exposure		Unless otherwise stated, assumes use at ambient temperature [ConsOC15]; assumes use in rooms up to 58m ³ [ConsOC11]; assumes use with typical ventilation [ConsOC8];
Section 2.1.1		Product categories
PC1:Adhesives, sealants--Glues, hobby use	OC	Covers concentrations up to 30% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 9g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 42/76

	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC1:Adhesives, sealants--Glues DIY-use (carpet glue, tile glue, wood parquet glue)	OC	Covers concentrations up to 0.2% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 6390g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 6.00hr/event[ConsOC14];
	RMM	No specific RMMs identified beyond those OCs stated
PC1:Adhesives, sealants--Glues DIY-use (carpet glue, tile glue, wood parquet glue); Tier 2: ConsExpo estimates (carpet glue as representative example)	OC	Covers concentrations up to 2% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 9000g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 53m3[ConsOC11]; for each use event, covers exposure up to 1.25hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC1:Adhesives, sealants--Glue from spray; Tier 2: ConsExpo estimates (spray glue)	OC	Covers concentrations up to 30% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC1:Adhesives, sealants--Sealants; Tier 2: ConsExpo estimates (assembly sealant as representative worst case)	OC	Covers concentrations up to 12% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 390g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC4_n:Anti-freeze and de-icing products--Washing car window	OC	Covers concentrations up to 1% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 0.5g [ConsOC2]; covers use in a one car garage (34 m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.02hr/event[ConsOC14];



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 43/76

	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC4_n:Anti-freeze and de-icing products--Pouring into radiator; Tier 2: ConsExpo estimates (all purpose cleaner (liquid), mixing and loading)	OC	Covers concentrations up to 10% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 2000g [ConsOC2]; covers use with open windows; for each use event, covers exposure up to 0.17 hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC4_n:Anti-freeze and de-icing products--Lock de-icer	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 4g [ConsOC2]; covers use in a one car garage (34 m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.25hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Waterborne latex wall paint; Tier 2: ConsExpo estimates (waterborne wall paint)	OC	Covers concentrations up to 1.5% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 3750g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Solvent rich, high solid, water borne paint; Tier 2: ConsExpo estimates (high solid paint as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 1300g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Aerosol spray can; Tier 2: ConsExpo estimates (spray can)	OC	Covers concentrations up to 25% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 44/76

		immediately with plenty of water. #1
PC9a:Coatings, paints, thinners,paint removers--Removers (paint-, glue-, wall paper-, sealant-remover); Tier 2: ConsExpo estimates (glue remover as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 2000g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 30m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM#1	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. #1
PC9c:Finger paints	OC	Covers concentrations up to 15% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, assumes swallowed amount of 1.35g [ConsOC13];
	RMM#1	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. #1
PC15_n: Non-metal surface treatment products--Waterborne latex wall paint; Tier 2: ConsExpo estimates (waterborne wall paint)	OC	Covers concentrations up to 1.5% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 3750g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM#1	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. #1
PC15_n: Non-metal surface treatment products--Solvent rich, high solid, water borne paint; Tier 2: ConsExpo estimates (high solid paint as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 1300g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM#1	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. #1
PC15_n: Non-metal surface treatment products--Aerosol spray can; Tier 2: ConsExpo estimates (spray can)	OC	Covers concentrations up to 25% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14];
	RMM#1	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. #1 Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 45/76

PC15_n: Non-metal surface treatment products--Removers (paint-, glue-, wall paper-, sealant-remover); Tier 2: ConsExpo estimates (glue remover as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 2000g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 30m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC18_n: Ink and toners--Inks and toners.	OC	Unless otherwise stated, covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 40g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC23_n: Leather tanning, dye, finishing, impregnation and care products--Polishes, wax / cream (floor, furniture, shoes); Tier 2: ConsExpo estimates (furniture polish as representative example)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 56g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC23_n: Leather tanning, dye, finishing, impregnation and care products--Polishes, spray (furniture, shoes); Tier 2: ConsExpo estimates (furniture leather spray as representative worst case)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 56g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 46/76

PC31:Polishes and wax blends-- Polishes, wax / cream (floor, furniture, shoes); Tier 2: ConsExpo estimates (furniture polish as representative worst case)	OC	Unless otherwise stated, covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 550g [ConsOC2]; covers use in rooms with open windows; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC31:Polishes and wax blends-- Polishes, spray (furniture, shoes); Tier 2: ConsExpo estimates (furniture leather spray as representative worst case)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC24:Lubricants, greases, release products		A use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing butan-1-ol has not been assumed.

^{#1} RMMs refer to qualitative assessment

9. ES6 – Use in cleaning agents (Industrial)

Section 1	Exposure Scenario Title
Title	Use in cleaning agents; CAS: 78-83-1
Use Descriptor	Sector of Use: Industrial (SU3)
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13
	Environmental Release Categories: ERC4



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 47/76

Processes, tasks, activities covered	Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.	
Section 2	Operational conditions and risk management measures	
Section 2.1	Control of worker exposure	
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC 17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases.#1 Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 48/76

General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Spraying [CS10].	7#2	Use in a spraying booth. Minimization of manual phases. #1 Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Rolling, Brushing [CS51].	10	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases.#1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 49/76

Dipping, immersion and pouring [CS4].	13	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
---------------------------------------	----	--

#1 refers to qualitative assessment

#2 other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)**10. ES6 – Use in cleaning agents (Professional)**

Section 1		Exposure Scenario Title
Title	Use in cleaning agents; CAS: 78-83-1	
Use Descriptor	Sector of Use: Professional (SU22)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13	
	Environmental Release Categories: ERC8a, ERC8d	
Processes, tasks, activities covered	Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand).	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC 17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 50/76

General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Rolling, Brushing [CS51].	10	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12]



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 51/76

		Use suitable eye protection and gloves [PPE14]. ^{#1}
Spraying [CS10].		Use in a spraying booth. Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
	11 ^{#2}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 47%) Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours Use suitable eye protection and gloves [PPE14]. ^{#1}
		Provide enhanced mechanical ventilation by mechanical means [E48].(effectiveness general ventilation: 47%) Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1} Wear a suitable respiratory protection (effectiveness: 80%). If no adequate respiratory protection is available, avoid carrying out operation for more than 2 hours.
Dipping, immersion and pouring [CS4].	13	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}

^{#1} refers to qualitative assessment



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 52/76

#² other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)**11.2. ES6 – Use in cleaning agents (Consumer)**

In general, it is assumed that there is no use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing isobutanol.

It is assumed that lubricants, greases usually are contained in closed systems in machines and other equipment.

Exposure arising from the use of machines and other equipment and arising from short and only occasional periods of manual handling (e.g. pouring of lubricants, greases) is considered to be negligible.

Section 1		Exposure Scenario Title
Title		Use in Cleaning Agents
Sector of Use (SU code)		21
Use Descriptor (PC codes)		PC4, PC9, PC24, PC35, PC38
Processes, tasks, activities covered		Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products.
Environmental Release Category		ERC8a, ERC8d
Specific Environmental Release Category		
Section 2		Operational conditions and risk management measures
Section 2.1		Control of consumer exposure
<i>Product characteristics</i>		
Physical form of product		liquid
Vapour pressure (Pa)		1600
Concentration of substance in product		Unless otherwise stated, covers concentration up to 50% [ConsOC1]
<i>Amounts used</i>		Unless otherwise stated, covers use amounts up to 3750g [ConsOC2];
<i>Frequency and duration of use/exposure</i>		Unless otherwise stated, covers use frequency up to 1 times per day [ConsOC4]; covers exposure up to 4 hours per event [ConsOC14]
<i>Other Operational Conditions affecting exposure</i>		Unless otherwise stated, assumes use at ambient temperature [ConsOC15]; assumes use in rooms up to 58m ³ [ConsOC11]; assumes use with typical ventilation [ConsOC8];
Section 2.1.1		Product categories
PC4_n:Anti-freeze and de-icing products--Washing car window	OC	Covers concentrations up to 1% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 0.5g [ConsOC2]; covers use in a one car garage (34 m ³) under typical ventilation [ConsOC10]; covers use in room size of 34m ³ [ConsOC11];



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 53/76

		for each use event, covers exposure up to 0.02hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC4_n:Anti-freeze and de-icing products--Pouring into radiator; Tier 2: ConsExpo estimates	OC	Covers concentrations up to 10% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 2000g [ConsOC2]; covers use with open windows; for each use event, covers exposure up to 0.17 hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC4_n:Anti-freeze and de-icing products--Lock de-icer	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 4g [ConsOC2]; covers use in a one car garage (34 m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.25hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Waterborne latex wall paint; Tier 2: ConsExpo estimates (waterborne wall paint)	OC	Covers concentrations up to 1.5% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 3750g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Solvent rich, high solid, water borne paint; Tier 2: ConsExpo estimates (high solid paint as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 1300g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 54/76

PC9a:Coatings, paints, thinners,paint removers--Aerosol spray can; Tier 2: ConsExpo estimates (spray can)	OC	Covers concentrations up to 25% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9a:Coatings, paints, thinners,paint removers--Removers (paint-, glue-, wall paper-, sealant-remover); Tier 2: ConsExpo estimates (glue remover as a representative worst case)	OC	Covers concentrations up to 4% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 2000g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 30m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC9c:Finger paints	OC	Covers concentrations up to 15% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, assumes swallowed amount of 1.35g [ConsOC13];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)-- Laundry and dish washing products	OC	Covers concentrations up to 5% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 15g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.50hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)-- Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Tier 2: ConsExpo estimates (floor cleaner (liquid) as a representative worst case; Mixing and loading)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 500g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; for each use event, covers exposure up to 0.0125hr/event[ConsOC14];



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 55/76

	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)-- Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Tier 2: ConsExpo estimates (floor cleaner (liquid) as a representative worst case; Application)	OC	Covers concentrations up to 6% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 880g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)-- Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Tier 2: ConsExpo estimates (bathroom cleaning spray as a representative worst case; Application (spraying))	OC	Covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use in room size of 10m3[ConsOC11]; for each use event, covers exposure up to 0.42hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)-- Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Tier 2: ConsExpo estimates (bathroom cleaning spray as a representative worst case; Application (leaving on and cleaning))	OC	Covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 30g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 10m3[ConsOC11]; for each use event, covers exposure up to 0.42hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 56/76

		immediately with plenty of water. ^{#1}
PC38_n: Welding and soldering products, flux products	OC	Unless otherwise stated, covers concentrations up to 10% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 12g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 1.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC24:Lubricants, greases, release products		A use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing butan-1-ol has not been assumed.

^{#1} RMMs refer to qualitative assessment**12. ES7 – Use in lubricants (Industrial)**

Section 1		Exposure Scenario Title
Title	Use in lubricants; CAS: 78-83-1	
Use Descriptor	Sector of Use: Industrial (SU3)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18	
	Environmental Release Categories: ERC4, ERC7	
Processes, tasks, activities covered	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 57/76

Human factors not influenced by risk management		<i>Not applicable</i>
Other Operational Conditions affecting worker exposure		Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (open systems) [CS16]. Batch process [CS55]. With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Spraying [CS10].	7#2	Use in a spraying booth. Minimization of manual phases. #1 Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 58/76

Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82].	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81].	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Pouring from small containers [CS9]. Dedicated facility [CS81].	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Rolling, Brushing [CS51].	10	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Dipping, immersion and pouring [CS4].	13	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Operation and lubrication of high energy open equipment [CS17].	17	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 59/76

	17 ^{#3}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 95%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Greasing, high energy. General exposures [CS1].	18	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
	18 ^{#3}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 95%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}

^{#1} refers to qualitative assessment^{#2} other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)^{#3} assessment at higher temperature/higher vapor pressure (>= 100 hPa); ECTOC TRA: high fugacity

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 60/76

9.13. ES7 – Use in lubricants (Professional)

Section 1		Exposure Scenario Title
Title	Use in lubricants; CAS: 78-83-1	
Use Descriptor	Sector of Use: Professional (SU22)	
	Process Categories: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20	
	Environmental Release Categories: ERC8a, ERC8d, ERC9a, ERC9b	
Processes, tasks, activities covered	Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC 17, PROC18)	
Contributing Scenarios		PROCs
		Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 61/76

General exposures (closed systems) [CS15]. ; Continuous process [CS54]. With sample collection [CS56]. ; Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Batch process [CS55]. ; With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (open systems) [CS16]. Batch process [CS55]. ; With sample collection [CS56].	4	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82]	8a	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81]	8b	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1
Pouring from small containers [CS9]. Dedicated facility [CS81]	9	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1
Rolling, Brushing [CS51].	10	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 62/76

Spraying [CS10].	11 ^{#2}	<p>Use in a spraying booth. Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}</p> <p>Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 47%) Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}</p> <p>Provide enhanced mechanical ventilation by mechanical means [E48].(effectiveness general ventilation: 47%) Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1} Wear a respirator with an effectiveness of 80%. If no adequate respirator is available, avoid carrying out operation for more than 2 hours.</p>
Dipping, immersion and pouring [CS4].	13	<p>Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}</p>



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 63/76

Operation and lubrication of high energy open equipment [CS17].	17	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
		Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 1 hour [OC11] Use suitable eye protection and gloves [PPE14]. #1
	17#3	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
		Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1 Wear a suitable respiratory protection (Effectiveness:90%)
Greasing, high energy. General exposures [CS1].	18	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
		Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 1 hour [OC11] Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 64/76

	18 ^{#3}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
		Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1} Wear a suitable respiratory protection (Effectiveness:90%)
Heat and pressure transfer (dispersive, closed system).	20	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}

^{#1} refers to qualitative assessment

^{#2} other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)

^{#3} assessment at higher temperature/higher vapor pressure (>= 100 hPa); ECTOC TRA: high fugacity

14. ES7 – Use in lubricants (Consumer)

In general, it is assumed that there is no use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing isobutanol.

It is assumed that lubricants, greases usually are contained in closed systems in machines and other equipment.

Exposure arising from the use of machines and other equipment and arising from short and only occasional periods of manual handling (e.g. pouring of lubricants, greases) is considered to be negligible.

Section 1		Exposure Scenario Title
Title		Use in Lubricants
Sector of Use (SU code)		21
Use Descriptor (PC codes)		PC1, (PC6) ^{#2} , PC24, PC31, PC35
Processes, tasks, activities covered		Covers the consumer use of formulated lubricants in closed and open systems including transfer operations, application, operation of engines and similar articles, equipment maintenance and disposal of waste oil.
Environmental Release Category		ERC8a, ERC8d ERC9a, ERC9b
Specific Environmental Release Category		
Section 2		Operational conditions and risk management measures



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 65/76

Section 2.1		Control of consumer exposure
Product characteristics		
Physical form of product		liquid
Vapour pressure (Pa)		1600
Concentration of substance in product		Unless otherwise stated, covers concentration up to 50% [ConsOC1]
Amounts used		Unless otherwise stated, covers use amounts up to 550g [ConsOC2];
Frequency and duration of use/exposure		Unless otherwise stated, covers use frequency up to 1 times per day [ConsOC4];covers exposure up to 4 hours per event [ConsOC14]
Other Operational Conditions affecting exposure		Unless otherwise stated, assumes use at ambient temperature [ConsOC15]; assumes use in rooms up to 58m ³ [ConsOC11]; assumes use with typical ventilation [ConsOC8];
Section 2.1.1		Product categories
PC1:Adhesives, sealants--Glues, hobby use	OC	Covers concentrations up to 30% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 9g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC1:Adhesives, sealants--Glues DIY-use (carpet glue, tile glue, wood parquet glue)	OC	Covers concentrations up to 0.2% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 6390g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 6.00hr/event[ConsOC14];
	RMM	No specific RMMs identified beyond those OCs stated
PC1:Adhesives, sealants--Glues DIY-use (carpet glue, tile glue, wood parquet glue); Tier 2: ConsExpo estimates (carpet glue as representative example)	OC	Covers concentrations up to 2% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 9000g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 53m ³ [ConsOC11]; for each use event, covers exposure up to 1.25hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 66/76

PC1:Adhesives, sealants--Glue from spray; Tier 2: ConsExpo estimates (spray glue)	OC	Covers concentrations up to 30% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC1:Adhesives, sealants--Sealants; Tier 2: ConsExpo estimates (assembly sealant as representative worst case)	OC	Covers concentrations up to 12% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 390g [ConsOC2]; covers use only in sufficiently ventilated rooms; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC31:Polishes and wax blends--Polishes, wax / cream (floor, furniture, shoes); Tier 2: ConsExpo estimates (furniture polish as representative worst case)	OC	Unless otherwise stated, covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 550g [ConsOC2]; covers use in rooms with open windows; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC31:Polishes and wax blends--Polishes, spray (furniture, shoes); Tier 2: ConsExpo estimates (furniture leather spray as representative worst case)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)--Laundry and dish washing products	OC	Covers concentrations up to 5% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 15g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.50hr/event[ConsOC14];



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 67/76

	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)--Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Tier 2: ConsExpo estimates (floor cleaner (liquid) as a representative worst case; Mixing and loading)	OC	Covers concentrations up to 50% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 500g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; for each use event, covers exposure up to 0.0125hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)--Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners); Tier 2: ConsExpo estimates (floor cleaner (liquid) as a representative worst case; Application)	OC	Covers concentrations up to 6% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 880g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 58m3[ConsOC11]; for each use event, covers exposure up to 4hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC35:Washing and cleaning products (including solvent based products)--Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Tier 2: ConsExpo estimates (bathroom cleaning spray as a representative worst case; Application (spraying))	OC	Covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; covers use in room size of 10m3[ConsOC11]; for each use event, covers exposure up to 0.42hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 68/76

PC35:Washing and cleaning products (including solvent based products)--Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) Tier 2: ConsExpo estimates (bathroom cleaning spray as a representative worst case; Application (leaving on and cleaning))	OC	Covers concentrations up to 20% [ConsOC1]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 30g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 10m3[ConsOC11]; for each use event, covers exposure up to 0.42hr/event[ConsOC14];
	RMM ^{#1}	Avoid contact with skin. After contact with skin, wash immediately with plenty of water. ^{#1} Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water. ^{#1}
PC24:Lubricants, greases, release products		A use by consumers which is related with intensive and direct handling of lubricants, greases (PC24) containing butan-1-ol has not been assumed.

^{#1} RMMs refer to qualitative assessment

^{#2} covered by PC31 and PC35

15. ES8 – Metal working fluids / rolling oils (Industrial)

Section 1		Exposure Scenario Title
Title	Metal working fluids / rolling oils; CAS: 78-83-1	
Use Descriptor	Sector of Use: Industrial (SU3)	
	Process Categories: PROC1, PROC2, PROC3, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17	
	Environmental Release Categories: ERC4	
Processes, tasks, activities covered	Covers the use in formulated MWFs/rolling oils including transfer operations, rolling and annealing activities, cutting/machining activities, automated and manual application of corrosion protections (including brushing, dipping and spraying), equipment maintenance, draining and disposal of waste oils.	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 69/76

Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	
Other Operational Conditions affecting worker exposure	Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)	
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. ; Continuous process [CS54]. With sample collection [CS56]. ; Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
General exposures (closed systems) [CS15]. Batch process [CS55]. ; With sample collection [CS56].	3	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Batch process [CS55]. Mixing operations (open systems) [CS30].	5	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 70/76

Spraying [CS10].	7 ^{#2}	Use in a spraying booth. Minimization of manual phases. ^{#1} Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines. Ensure that the task is being carried out outside the breathing zone of a worker. Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82]	8a	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81]	8b	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 97%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Pouring from small containers [CS9]. Dedicated facility [CS81]	9	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Rolling, Brushing [CS51].	10	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}
Dipping, immersion and pouring [CS4].	13	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 71/76

Operation and lubrication of high energy open equipment [CS17].	17	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
	17 ^{#3}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 95%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1

#1 refers to qualitative assessment

#2 other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)

#3 assessment at higher temperature/higher vapor pressure (>= 100 hPa); ECTOC TRA: high fugacity

16. ES8 – Metal working fluids / rolling oils (Professional)

Section 1		Exposure Scenario Title
Title	Metal working fluids / rolling oils; CAS: 78-83-1	
Use Descriptor	Professional (SU22)	
	Process Categories: PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC17	
	Environmental Release Categories: ERC8a	
Processes, tasks, activities covered	Covers the use in formulated MWFs including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.	
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product	Liquid, vapour pressure 0.5 - 10 kPa [OC4].	
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently) [G13].	
Amounts used	<i>Not applicable</i>	
Frequency and duration of use	Covers daily exposures up to 8 hours (unless stated differently) [G2]	
Human factors not influenced by risk management	<i>Not applicable</i>	



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 72/76

Other Operational Conditions affecting worker exposure		Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC 17, PROC18)
Contributing Scenarios	PROCs	Risk Management Measures
General exposures (closed systems) [CS15]. Continuous process [CS54].	1	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Continuous process [CS54]. With sample collection [CS56]. Equipment cleaning and maintenance [CS39].	2	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
General exposures (closed systems) [CS15]. Batch process [CS55]. With sample collection [CS56].	3	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
Batch process [CS55]. Mixing operations (open systems) [CS30].	5	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Non-dedicated facility [CS82]	8a	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1
Transfer from/pouring from containers [CS22]. Dedicated facility [CS81]	8b	Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. #1



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 73/76

Rolling, Brushing [CS51].	10	<p>Minimization of manual phases. #1</p> <p>Avoid frequent and direct contact with substance. #1</p> <p>Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1</p> <p>Avoid carrying out operation for more than 4 hours [OC12]</p> <p>Use suitable eye protection and gloves [PPE14]. #1</p>
Spraying [CS10].	11 ^{#2}	<p>Use in a spraying booth.</p> <p>Minimization of manual phases. #1</p> <p>Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines.</p> <p>Ensure that the task is being carried out outside the breathing zone of a worker.</p> <p>Avoid frequent and direct contact with substance. #1</p> <p>Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1</p> <p>Use suitable eye protection and gloves [PPE14]. #1</p> <hr/> <p>Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 47%)</p> <p>Minimization of manual phases. #1</p> <p>Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines.</p> <p>Avoid frequent and direct contact with substance. #1</p> <p>Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1</p> <p>Avoid carrying out operation for more than 4 hours [OC12]</p> <p>Use suitable eye protection and gloves [PPE14]. #1</p> <hr/> <p>Provide enhanced mechanical ventilation by mechanical means [E48].(effectiveness general ventilation: 47%)</p> <p>Minimization of manual phases. #1</p> <p>Clean equipment and the work area every day [C&H3]. Regular inspection and maintenance of equipment and machines.</p> <p>Avoid frequent and direct contact with substance. #1</p> <p>Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1</p> <p>Use suitable eye protection and gloves [PPE14]. #1</p> <p>Wear a suitable respiratory protection (effectiveness: 80%). If no adequate respirator is available, avoid carrying out operation for more than 2 hours.</p>
Dipping, immersion and pouring [CS4].	13	<p>Minimization of manual phases. #1</p> <p>Avoid frequent and direct contact with substance. #1</p> <p>Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1</p> <p>Avoid carrying out operation for more than 4 hours [OC12]</p> <p>Use suitable eye protection and gloves [PPE14]. #1</p>



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4 Last up date:10.03.2017 Date issued: January, 2011 Page 74/76

Operation and lubrication of high energy open equipment [CS17].	17	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
		Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Avoid carrying out operation for more than 1 hour [OC11] Use suitable eye protection and gloves [PPE14]. #1
	17 ^{#3}	Provide extract ventilation to points where emissions occur [E54]. (effectiveness LEV: 90%) Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1
		Minimization of manual phases. #1 Avoid frequent and direct contact with substance. #1 Supervision in place to check that the RMMs in place are being used correctly and OCs followed. #1 Use suitable eye protection and gloves [PPE14]. #1 Wear a suitable respiratory protection (Effectiveness:90%)

^{#1} refers to qualitative assessment

^{#2} other Tool used: Stoffenmanager (v. 4.0; 75th percentile for long term assessment)

^{#3} assessment at higher temperature/higher vapor pressure (>= 100 hPa); ECTOC TRA: high fugacity

17. ES9 – Use as consumer care product or disinfectant (Consumer)

In general, the use of perfumes, fragrances (PC28) and cosmetics, personal care products (PC 39) are considered to be covered by other legislations.



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH
Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 75/76

19.ES10 – Use in laboratories (Professional)

Section 1		Exposure Scenario Title
Title		Use in laboratories; CAS: 78-83-1
Use Descriptor		Sector of Use: Professional (SU22)
		Process Categories: PROC10, PROC15
		Environmental Release Categories: ERC8a
Processes, tasks, activities covered		Use of small quantities within laboratory settings, including material transfers and equipment cleaning
Section 2		Operational conditions and risk management measures
Section 2.1		Control of worker exposure
Product characteristics		
Physical form of product		Liquid, vapour pressure 0.5 - 10 kPa [OC4].
Concentration of substance in product		Covers percentage substance in the product up to 100 % (unless stated differently) [G13].
Amounts used		<i>Not applicable</i>
Frequency and duration of use		Covers daily exposures up to 8 hours (unless stated differently) [G2]
Human factors not influenced by risk management		<i>Not applicable</i>
Other Operational Conditions affecting worker exposure		Assumes a good basic standard of occupational hygiene is implemented [G1]. Assumes activities are at ambient temperature (unless stated differently) [G17]. Operation is carried out at elevated temperature (> 20°C above ambient temperature) [OC7]. (PROC17, PROC18)
Contributing Scenarios	PROCs	Risk Management Measures
Rolling, Brushing [CS51].	10	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Avoid carrying out operation for more than 4 hours [OC12] Use suitable eye protection and gloves [PPE14]. ^{#1}
Laboratory activities [CS36]. Small scale [CS61].	15	Minimization of manual phases. ^{#1} Avoid frequent and direct contact with substance. ^{#1} Supervision in place to check that the RMMs in place are being used correctly and OCs followed. ^{#1} Use suitable eye protection and gloves [PPE14]. ^{#1}

^{#1} refers to qualitative assessment

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011

SAFETY DATA SHEET-extended

Prepared in accordance with Commission Regulation (EU) 830/2015, amending Regulation (EC) 1907/2006, REACH

Iso-BUTANOL

Revision: 4

Last up date:10.03.2017

Date issued: January, 2011

Page 76/76



This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.

Code: FDS 011